

# Telescopic drywall support ST

Provides real support during roof assembly



Simply better.



## Flexible in application

It enables the positioning and holding of plaster carton, wooden planks, panels, battens, metal bars, foils and lamp bodies, for example. The support can even be used on sloping roofs:

- due to stable steel pipe construction in three sizes – telescoping up to 2.90 m
- due to 8.5 x 6.5 cm base plates with a swivel range of -45° to +45°



## Easy to handle


The support can be used quickly:

- due to the fixing in just two steps: The rough pre-setting is carried out using the telescoping and quickly locking inner pipe; the final clamping is carried out by turning the support at the foam grip

## Secure hold

Resilient and anti-slip, the support guarantees secure holding, even on sensitive surfaces:


- due to special steel pipes for a maximum load bearing capacity of up to 60 kg
- due to additional locking of the release button
- due to rubber contact surfaces top and bottom



## Telescopic drywall support ST

Order-No.	Adjusting range mm	Load limit max. kg	kg	qty.	V3
ST125	750-1250	60	1.50	10	
ST250	1450-2500	60	2.20	10	
ST290	1600-2900	50	2.40	10	

For further information  
[www.bessey.de](http://www.bessey.de)



BESSEY Tool GmbH & Co. KG ■ Mühlwiesenstraße 40  
74321 Bietigheim-Bissingen, Germany

Your dealer:

official distributor of **BESSEY Tool** in Ukraine  
**CLL GRN-GROUP**  
+38 067 67 203 23  
[info@grn-group.com.ua](mailto:info@grn-group.com.ua)  
<https://www.grn-group.com.ua/>